



USQT.S309 - Extinguishing System Attachments

Extinguishing System Attachments

See General Information for Extinguishing System Attachments

POTTER ELECTRIC SIGNAL CO L L C

1609 PARK 370 PL

HAZELWOOD, MO 63042-4417 USA

S309

SPRINKLER SYSTEM ALARM INITIATING DEVICES

WET PIPE, PADDLE TYPE

Model	Size In.	Pipe Schedule	Max System Pressure psig
VSG	2, 2-1/2, 3, 4	Water Mist	450
		Systems Only	
VSR-F, VSR-FE,	2, 2-1/2, 3,	10-40	450
VSR-FE-2, VS-F	3-1/2, 4, 5,	Steel	
	6, 8, 10		
VSR, VSR-CR	2, 2-1/2, 3, 3-1/2,	10-40 Steel	450
	4, 5, 6, 8, 10		
VSR-AT	2, 2-1/2, 3, 3-1/2,	10-40 Steel	450
	4, 5, 6, 8		
VSR-EU	2, 2-1/2, 3, 4, 5, 6, 8	10-40 Steel	450
VSR-S, VSR-S (EU)	1, 1-1/4, 1-1/2, 2	10-40 Steel	300
		Listed Plastic	
		K, L, M Copper	
VSR-SF, VS-SP, VS-SPB	1, 1-1/4, 1-1/2, 2	10-40 Steel	250
		Listed Plastic	
		K, L, M Copper	
VSR-CF, VSR-C	2, 2-1/2, 3,	Listed Plastic	175
	2, 2-1/2, 3, 4	K,L,M Copper	
VSR-SFG, VSR-SG, VSR-SFT, VSR-ST	1, 1-1/4, 1-1/2, 2	Listed Plastic	250

Model VS-SP, VS-SPB for outdoor use with Kit No. 1940037. Models VS-F, VSR-F, VSR-CF, VSR-C, VSR-FE, VSR-FE-2 for outdoor use with Kit No. 1940036.

DRY-PIPE & WET-PIPE, PRESSURE TYPE

Model	Oper Pressure psig	Max System Pressure psig
*PS-10	0-20	300
*PS-10A	4-8	300
*PS-100	20-225	300
*PS10-1	4-15	300
*PS10-1A	4-20	250
*PS10-2	4-15	300
*PS10-2A	4-20	250
*PS10-1 w/Brass Bushing	4-15	300
*PS10-2 w/Brass Bushing	4-15	300
*PS-100A	20-175	300
*PS100-2	25-175	300
*PS100-2A	20-225	300
WFS-B	10	250
WFSPDB	100	250
*WFSR-C	10	250
*WFSR-F	4-8	175
QRS	10-65	175

SUPERVISORY SIGNAL INITIATING DEVICES

PRESSURE DEVICES

Model	Oper Pressure psig	Max System Pressure psig
*PS-40	20-225	300
PS15-2	5-30	300
*PS-40A	20-175	300
*PS40-1	10-60	300
*PS40-1A	20-175	300
*PS40-2A	20-175	300
*PS25-2	10-60	300
*PS40-2	10-60	300
*PS40-1 w/Brass Bushing	10-60	300
*PS40-2 w/Brass Bushing	10-60	300

HLS-B	40	250
*PS-120	20-225	300
*PS-120A	20-175	300
*PS120-1	25-175	300
*PS120-1A	20-175	300
*PS120-2	25-175	250
*PS120-2A	20-175	300
*PS120-1 w/Brass Bushing	35-225	300
*PS120-2 w/Brass Bushing	35-225	300

CONTROL VALVE DEVICES

Gate Valve	Post Indicator Valve
GVS	PIVS-B
OSYS-B	
*OSYSU-1, -2	*PCVS-1, -2

Accessory, Cover Tamper Switch Kit, Model PSCTSK for use with the PS Series Pressure Switches.

PTS-B Plug Type Switch — Special Application

*PMS Plug Type Switch — Special Application

*PTS-C Plug Type Switch — Special Application.

BVS-1", -3/4", -1/2" Supervised Trim Valves.

RBVS — Retro-fit Ball Valve Supervisory Switch.

SUPERVISORY WATER TEMPERATURE DEVICES Steel or Wood Tank

*TTS-S, TTS-W

SUPERVISORY AIR TEMPERATURE DEVICES

RTS-C, RTS-O, for indoor use.

WATERLEVEL DEVICES

*WLS-S (Steel Tank), WLS-W (Wood Tank), WCS

*For indoor or outdoor use.

Last Updated on 2020-05-04

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"